

# Moving from Temporal Coherence to Decorrelation Time of Interferometric Measurements Exploiting ESA's SAR Archive

Michael Foumelis<sup>1</sup>, Zinovia Mitraka<sup>2</sup>, Roberto Cuccu<sup>3,4</sup>, Yves-Louis Desnos<sup>5</sup>, Marcus Engdahl<sup>5</sup>

<sup>1</sup>RSAC c/o ESA-ESRIN, Science, Applications and Future Technologies Department, Via Galileo Galilei, 00044 Frascati, Italy - michael.foumelis@esa.int

<sup>2</sup>Foundation for Research and Technology – Hellas (FORTH), N. Plastira 100, Vassilika Vouton, 70013 Heraklion, Greece - mitraka@iacm.forth.gr

<sup>3</sup>ESA Research and Service Support, Via Galileo Galilei, 00044 Frascati, Italy - roberto.cuccu@esa.int

<sup>4</sup>Progressive Systems Srl, Parco Scientifico di Tor Vergata, 00133 Roma, Italy

<sup>5</sup>ESA-ESRIN, Science, Applications and Future Technologies Department, Via Galileo Galilei, 00044 Frascati, Italy - yves-louis.desnos@esa.int, marcus.engdahl@esa.int

**THEME:** InSAR Applications – Thematic mapping, vegetation and DEMs

**KEY WORDS:** Decorrelation Time, Temporal Coherence, SAR interferometry, Geostatistical Analysis

## ABSTRACT

Following a plethora of validations and demonstrations SAR Interferometry (InSAR) has been established as a mature space geodetic technique for providing valuable insights for various phenomena related to geohazards. One of the main advantages of space borne SAR systems with respect to GNSS is the continuous spatial coverage. However, the impact of temporal decorrelation especially in repeat-pass interferometry has been observed during the historical development of InSAR applications. Interferometric coherence can be considered as expression of temporal decorrelation. It is understood that interferometric coherence decreases with time between SAR acquisitions because of changes in surface reflectivity, reducing the quality of SAR phase measurements. This is an intrinsic characteristic of the design of SAR systems that has a significant contribution at longer time scales. Since the majority of geohazards rely on long term observation scenarios, the effect of temporal decorrelation is evident as coherence becomes dominated by temporal changes. Although in the past there was not sufficient amount of SAR data to extract robust statistical metrics, in the present study it is demonstrated that tailored analysis of interferometric coherence by exploiting the large SAR archive as well as data from operational missions such as the Sentinels, available by the European Space Agency (ESA), enables the accurate quantification of temporal decorrelation. A methodology to translate the observed rate of coherence loss into decorrelation times over two volcanic landscape, namely the Santorini volcanic complex and Mt. Etna is the subject treated in this study. Specifically, a sensitivity analysis was performed on a large data stack of interferometric pairs to quantify at a pixel level the time beyond which the interferometric phase becomes practically unusable due to decorrelation. The estimation and mapping within a geostatistical context of the spatial distribution of the temporal decorrelation times in an area without a necessary a priori knowledge of its surface characteristics is a fundamental parameter for the design and establishment of local GNSS networks as well as the definition of optimal monitoring strategy for various geohazards. The dependence of decorrelation on various land cover/use types is also analysed by post-processing in a GIS environment. Though the dependence of decorrelation on various land cover/use types is already documented the provision of additional information regarding the expected time of decorrelation is of practical use especially when EO data are utilized in operational activities. The performed analysis is viewed within the improved capacity of current and future SAR systems, while underlining the necessity for exploitation of archive data.

